

1 Identification

- **Product identifier**
 - *Product number* YBA600
 - *Trade name:* **INSULATOR FOR EXTERIOR**
 - *Application of the substance / the mixture* For professional use
- **Details of the supplier of the safety data sheet**
 - *Manufacturer/Supplier:*
IVM Chemicals srl
Viale della Stazione 3 - 27020 Parona (PV) Italy tel +39 038425441
 - *Information department:*
Environmental Health and safety office
hseoffice@ivmchemicals.com
 - *Emergency telephone number:*
ChemTel Expert Assistance Hotline/SDS Fax Access by dialing 1-800-255-3924 or for International +1-813-248-0585.

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- *GHS label elements*

The product is classified and labeled according to the Globally Harmonized System (GHS).

- *Hazard pictograms*



GHS02



GHS07



GHS08

- *Signal word* Danger

- *Hazard-determining components of labeling:*

xylene

ethylbenzene

toluene

methyl methacrylate

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 1)

· Hazard statements

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = *1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

3 Composition/information on ingredients

· Chemical characterization: Mixtures

- Description: Mixture: consisting of the following components.

· Dangerous components:

1330-20-7	xylene  Flam. Liq. 3, H226  STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	25-29.9%
123-86-4	n-butyl acetate  Flam. Liq. 3, H226  STOT SE 3, H336	15- <50%
110-19-0	isobutyl acetate  Flam. Liq. 2, H225	5-9.99%

(Contd. on page 3)

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 2)

100-41-4	ethylbenzene  Flam. Liq. 2, H225  Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304  Acute Tox. 4, H332	5-9.99%
108-88-3	toluene  Flam. Liq. 2, H225  Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336 Aquatic Chronic 3, H412	2.5-4.99%
108-32-7	propylene carbonate  Eye Irrit. 2A, H319	1-2.49%
80-62-6	methyl methacrylate  Flam. Liq. 2, H225  Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	1-2.49%
64-17-5	ethanol  Flam. Liq. 2, H225	0.5-1%
868-77-9	2-hydroxyethyl methacrylate  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	0.5-<1%

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Take off immediately all contaminated clothing, include underwear and shoes (if necessary).

Rinse thoroughly with plenty of water for at least 20 minutes and take medical advise. If medical advise is needed have products container or label at hand.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by substances, refer to Section 11.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents: Alcohol resistant foam, CO, powder, water spray/mist.

· For safety reasons unsuitable extinguishing agents:

Do not use a jet water stream as it may scatter and spread fire.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 4)

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 3)

- **Advice for firefighters**

Cool by spraying with water the containers to prevent product decomposition and the development of substances potentially hazardous for health and also, in the case of closed containers exposed to flames to prevent explosions.

- **Protective equipment:**

Hardhat with visor, fireproof clothing, suitable gloves and if necessary respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to Section 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

· PAC-1:		
1330-20-7	xylene	130 ppm
123-86-4	n-butyl acetate	5 ppm
110-19-0	isobutyl acetate	450 ppm
100-41-4	ethylbenzene	33 ppm
108-88-3	toluene	67 ppm
108-32-7	propylene carbonate	34 mg/m ³
80-62-6	methyl methacrylate	17 ppm
64-17-5	ethanol	1,800 ppm
141-78-6	ethyl acetate	1,200 ppm
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m ³
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
· PAC-2:		
1330-20-7	xylene	920* ppm
123-86-4	n-butyl acetate	200 ppm
110-19-0	isobutyl acetate	1300* ppm
100-41-4	ethylbenzene	1100* ppm
108-88-3	toluene	560 ppm
108-32-7	propylene carbonate	370 mg/m ³
80-62-6	methyl methacrylate	120 ppm
64-17-5	ethanol	3300* ppm
141-78-6	ethyl acetate	1,700 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m ³

(Contd. on page 5)

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 4)

1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
· PAC-3:		
1330-20-7	xylene	2500* ppm
123-86-4	n-butyl acetate	3000* ppm
110-19-0	isobutyl acetate	7500** ppm
100-41-4	ethylbenzene	1800* ppm
108-88-3	toluene	3700* ppm
108-32-7	propylene carbonate	2,200 mg/m3
80-62-6	methyl methacrylate	570 ppm
64-17-5	ethanol	15000* ppm
141-78-6	ethyl acetate	10000** ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m3
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm

7 Handling and storage

· Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool, well-ventilated area, away from heat and sources of ignition

Provide solvent resistant, sealed floor.

Observe the label precautions, the expiration date for the use, if not indicated, is from delivery date of goods.

In cases where there is no reported expiration date, it means that the product must be used within 8 months.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) Those typical of the product and the instructions in the data sheet if required.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

(Contd. on page 6)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 12/13/2016

Version number 57

Reviewed on 12/09/2016

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 5)

At this time, the other constituents have no known exposure limits.

123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m , 150 ppm
REL	Short-term value: 950 mg/m , 200 ppm Long-term value: 710 mg/m , 150 ppm
TLV	Short-term value: 712 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm

110-19-0 isobutyl acetate

PEL	Long-term value: 700 mg/m , 150 ppm
REL	Long-term value: 700 mg/m , 150 ppm
TLV	Short-term value: 172 mg/m , 150 ppm Long-term value: 238 mg/m , 50 ppm

100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m , 100 ppm
REL	Short-term value: 545 mg/m , 125 ppm Long-term value: 435 mg/m , 100 ppm
TLV	Long-term value: 87 mg/m , 20 ppm BEI

80-62-6 methyl methacrylate

PEL	Long-term value: 410 mg/m , 100 ppm
REL	Long-term value: 410 mg/m , 100 ppm
TLV	Short-term value: 410 mg/m , 100 ppm Long-term value: 205 mg/m , 50 ppm DSEN

· Ingredients with biological limit values:**1330-20-7 xylene**

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

100-41-4 ethylbenzene

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

(Contd. on page 7)

US

Product number YBA600
Trade name: INSULATOR FOR EXTERIOR

(Contd. of page 6)

108-88-3 toluene

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.
- Pregnant women should strictly avoid inhalation or skin contact.

· Breathing equipment:

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Protective gloves

Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The glove material has to be impermeable and resistant to the product .

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Tightly sealed goggles

US

(Contd. on page 8)

Product number YBA600
Trade name: INSULATOR FOR EXTERIOR

(Contd. of page 7)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:

Fluid

· Color:

According to product specification

· Odor:

Characteristic

· Odor threshold:

Not determined.

· pH-value:

Not determined.

· Change in condition

· Melting point/Melting range:

Undetermined.

· Boiling point/Boiling range:

78 °C (172 °F)

· Flash point:

4 °C (39 °F)

· Flammability (solid, gaseous):

Not applicable.

· Ignition temperature:

370 °C (698 °F)

· Decomposition temperature:

Not determined.

· Auto igniting:

Product is not selfigniting.

· Danger of explosion:

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

· Lower:

1.0 Vol %

· Upper:

12.5 Vol %

· Vapor pressure at 20 °C (68 °F):

47 hPa (35 mm Hg)

· Density at 20 °C (68 °F):

0.964 g/cm (8.045 lbs/gal)

· Relative density

Not determined.

· Vapor density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· Water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water):

Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C (68 °F):

55 s (ISO 6 mm)

· Oxidising properties:

N.A.

· Solvent content:

· VOC content:

64.4 %

620.5 g/l / 5.18 lb/gl

· Solids content:

33.8 %

· Other information (HAPS)

1330-20-7	xylene	25-29.9%
100-41-4	ethylbenzene	5-9,99%
108-88-3	toluene	2,5-4,99%
80-62-6	methyl methacrylate	1-2,49%
1330-20-7	xylene	0.1-<0.5%

(Contd. on page 9)

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 8)

· **Other information**

No further relevant information available.

10 Stability and reactivity

- **Reactivity** typical of the product as indicated in the data sheet
 - **Chemical stability** The product is stable in normal conditions of storage and use recommended
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Reacts with strong acids and oxidizing agents.
Vapours may form explosive mixtures with air
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****1330-20-7 xylene**

Oral	LD50	3523 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	1701 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

123-86-4 n-butyl acetate

Oral	LD50	10760 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	14000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	21.1 mg/l (rat/szczur/mouse/souris/Maus/ratón)

110-19-0 isobutyl acetate

Oral	LD50	13400 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	17401 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	31 mg/l (rat/szczur/mouse/souris/Maus/ratón)

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	15486 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	17.2 mg/l (rat/szczur/mouse/souris/Maus/ratón)

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	12124 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	25.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)

108-32-7 propylene carbonate

Oral	LD50	5001 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	2001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

80-62-6 methyl methacrylate

Oral	LD50	7872 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	5001 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)

(Contd. on page 10)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 12/13/2016

Version number 57

Reviewed on 12/09/2016

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 9)

Inhalative	LC50/4 h	78 mg/l (rat/szczur/mouse/souris/Maus/ratón)
64-17-5 ethanol		
Oral	LD50	10470 mg/kg (rat/szczur/mouse/souris/Maus/ratón)
Dermal	LD50	20000 mg/kg (rabbit/królik/Kaninchen/conejo/lapin)
Inhalative	LC50/4 h	124.7 mg/l (rat/szczur/mouse/souris/Maus/ratón)
868-77-9 2-hydroxyethyl methacrylate		
Oral	LD50	5050 mg/kg (rat/szczur/mouse/souris/Maus/ratón)

- **Primary irritant effect:**
 - *on the skin:* Irritant to skin and mucous membranes.
 - *on the eye:* Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
 - Causes skin irritation.
 - Causes serious eye irritation.
 - May cause an allergic skin reaction.
 - Suspected of damaging the unborn child.
 - May cause respiratory irritation.
 - May cause damage to organs through prolonged or repeated exposure.
 - Irritant
- **Carcinogenic categories**
 - Ethylbenzene
 - From IARC MONOGRAPHS VOLUME 77/2000
 - Human carcinogenicity data
 - Two studies of workers potentially exposed to ethylbenzene in a production plant and a styrene polymerization plant were available. In the first study, no excess of cancer incidence was found but the description of methods was insufficient to allow proper evaluation of this finding. In the second study, no cancer mortality excess was observed during the follow-up of 15 years.
- Evaluation
 - There is inadequate evidence in humans for the carcinogenicity of ethylbenzene. There is sufficient evidence in experimental animals for the carcinogenicity of ethylbenzene.

· IARC (International Agency for Research on Cancer - Cl. 1 and 2)		
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
108-88-3	toluene	3
80-62-6	methyl methacrylate	3
64-17-5	ethanol	1
1330-20-7	xylene	3

· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

US

(Contd. on page 11)

Product number YBA600
Trade name: INSULATOR FOR EXTERIOR

(Contd. of page 10)

12 Ecological information

· Toxicity

· Aquatic toxicity:	
123-86-4 n-butyl acetate	
EC50	648 mg/l (algae) (72 h) 44 mg/l (daphnia) (48 h)
LC50 (96h)	18 mg/l (Fish)
110-19-0 isobutyl acetate	
EC50	370 mg/l (algae) (72 h) 25 mg/l (daphnia)
LC50 (96h)	17 mg/l (Fish)
100-41-4 ethylbenzene	
EC50	75 mg/l (daphnia) (48 h)
108-88-3 toluene	
EC50	134 mg/l (algae) (3 h) 3.78 mg/l (daphnia) (48 h) 58 mg/l (Fish)
108-32-7 propylene carbonate	
EC50	901 mg/l (algae) (72 h) 1001 mg/l (daphnia) (48 h)
LC50 (96h)	1001 mg/l (Fish)
80-62-6 methyl methacrylate	
EC50	170 mg/l (algae) (72 h)
LC50 (96h)	191 mg/l (Fish)
64-17-5 ethanol	
EC50	5012 mg/l (daphnia) (48 h)
LC50 (96h)	15.3 mg/l (Fish)
868-77-9 2-hydroxyethyl methacrylate	
LC50 (96h)	240 mg/l (Fish)

· Persistence and degradability

Data refers to the substance Toluene CAS No. 108-88-3
 Readily biodegradable (according to OECD criteria)

· Behavior in environmental systems:

- *Bioaccumulative potential* No further relevant information available.
- *Mobility in soil* No further relevant information available.

· Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.

- **Other adverse effects** No further relevant information available.

US

(Contd. on page 12)

Product number YBA600
Trade name: INSULATOR FOR EXTERIOR

(Contd. of page 11)

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to hazardous waste disposers.

Dispose of contents and container in accordance with local state and federal regulations.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **DOT** NA1263
 - **IMDG, IATA** UN1263

- **UN proper shipping name**

- **DOT** Paint
 - **IMDG, IATA** PAINT

- **Transport hazard class(es)**

- **DOT**



- **Class** 3 Flammable liquids
 - **Label** 3
 - **Class** 3 Flammable liquids
 - **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids
 - **Label** 3

- **Packing group**

- **DOT, IMDG, IATA** III

- **Environmental hazards:**

- **Marine pollutant:** No

- **Special precautions for user**

Warning: Flammable liquids

- **Danger code (Kemler):** -

- **EMS Number:** F-E, S-E

- **Stowage Category** A

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

(Contd. on page 13)

Safety Data Sheet

29 CFR Parts 1910 1915 1926

Printing date 12/13/2016

Version number 57

Reviewed on 12/09/2016

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 12)

· Transport/Additional information:**· IMDG**

- Limited quantities (LQ)
- Excepted quantities (EQ)

5L

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

15 Regulatory information**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

Requirements of Federal Register

· SARA**· Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings) :

1330-20-7	xylene	25-29.9%
100-41-4	ethylbenzene	5-9,99%
108-88-3	toluene	2,5-4,99%
80-62-6	methyl methacrylate	1-2,49%
1330-20-7	xylene	0.1-<0.5%
78-93-3	butanone	<0.1%

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65**· Chemicals known to cause cancer:**

100-41-4	ethylbenzene	* 5-9,99%
----------	--------------	-----------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene	2,5-4,99%
64-17-5	ethanol	0,5-1%

· Carcinogenic categories**· EPA (Environmental Protection Agency)**

1330-20-7	xylene	I	25-29.9%
100-41-4	ethylbenzene	D	5-9,99%
108-88-3	toluene	II	2,5-4,99%
80-62-6	methyl methacrylate	E, NL	1-2,49%
1330-20-7	xylene	I	0.1-<0.5%

(Contd. on page 14)

Product number YBA600**Trade name: INSULATOR FOR EXTERIOR**

(Contd. of page 13)

78-93-3	butanone	1	<0.1%
---------	----------	---	-------

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
108-88-3	toluene	A4
80-62-6	methyl methacrylate	A4
64-17-5	ethanol	A3
1330-20-7	xylene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** IVM Chemicals Srl

- **Contact:** See emergency phone

· **Date of preparation / last revision** 12/13/2016 / 56

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids . Category 2

Flam. Liq. 3: Flammable liquids . Category 3

Acute Tox. 4: Acute toxicity . Category 4

Skin Irrit. 2: Skin corrosion/irritation . Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation . Category 2A

Skin Sens. 1: Skin sensitisation . Category 1

Carc. 2: Carcinogenicity . Category 2

Carc. 2: Carcinogenicity . Category 2

Repr. 2: Reproductive toxicity . Category 2

STOT SE 3: Specific target organ toxicity (single exposure) . Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) . Category 2

Asp. Tox. 1: Aspiration hazard . Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard . Category 3

· **Sources**

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL and following amendments

Directive 67/548/EEC and following amendments and adjustments

(Contd. on page 15)



Safety Data Sheet
29 CFR Parts 1910 1915 1926

Printing date 12/13/2016

Version number 57

Reviewed on 12/09/2016

Product number YBA600

Trade name: INSULATOR FOR EXTERIOR

(Contd. of page 14)

Agency ECHA web site

INRS Fiche Toxicologique

IARC International agency for research on cancer

· * *Data compared to the previous version altered.*

US